

1129.00 EUR  
incl. 19% VAT, plus [shipping](#)



- 17.0" 350 nits high brightness SVGA TFT LCD with LED backlight
- Onboard Intel® Q170 Express Chipset
- Supports Intel LGA 1151 Socket Core™ i3, i5, i7 & Pentium Processors
- 2\* Dual Channel DDR4 2133MHz up to 32GB
- Support Dual Intel® Gigabit LAN
- Support 4 \* COM ports (COM1/3 Support RS232/422/485)
- Support 6\*USB3.0 Ports
- Support 2.5" SATA HDD, 1 \* M-SATA connector
- Support 1\*PCI or PCI-Ex16 , 2 \* Mini PCI-E
- Plastic and IP65-rated front bezel

## Display

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| Front Bezel         | - IP65, NEMA 4 rugged protection, metal front bezel |
| Display Type        | - 17.0" With LED Backlight                          |
| Brightness (cd/m²)  | - 350 nits                                          |
| Display Color       | - 262K                                              |
| Resolution          | - 1280 x1024 @ 60Hz                                 |
| Viewing Angle (H/V) | - 170°/160°                                         |

|                            |                                                                                                                                                                                                                        |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pixel Pitch                | - 0.264 x 0.264 mm                                                                                                                                                                                                     |
| Aspect Ratio               | - 4:3                                                                                                                                                                                                                  |
| Contrast Ratio             | - 1000:1                                                                                                                                                                                                               |
| Response Time              | - 3.5 ms                                                                                                                                                                                                               |
| <b>Touch screen</b>        |                                                                                                                                                                                                                        |
| Type                       | - 5 wires analog resistive type                                                                                                                                                                                        |
| Active Range               | - 337.00 x 269.50mm ±0.2mm                                                                                                                                                                                             |
| Transparency               | - 80 ±3%                                                                                                                                                                                                               |
| Operating Force            | - ■ 80g                                                                                                                                                                                                                |
| Knock test                 | - 10,000,000 times keystrokes                                                                                                                                                                                          |
| <b>Main System</b>         |                                                                                                                                                                                                                        |
| CPU                        | - Intel® LGA1151 Socket                                                                                                                                                                                                |
| RAM                        | - DDR4 2133MHz Max 32GB                                                                                                                                                                                                |
| BIOS                       | - 128MB SPI Flash ROM                                                                                                                                                                                                  |
| Storage                    | - 1 * 2.5" SATA HDD<br>- 1 * M-SATA connector                                                                                                                                                                          |
| Watchdog Timer             | - 255 levels, 0~255 sec.                                                                                                                                                                                               |
| OS Support                 | - Windows 7 / 8.1 / 10 / Linux                                                                                                                                                                                         |
| <b>I/O Connector</b>       |                                                                                                                                                                                                                        |
| I/O Ports and Switches     | - 6 * USB3.0<br>- 2 * RS232<br>- 2 * RS232/422/485<br>- 1 * DVD-D,HDMI,DP<br>- 2 * LAN (Intel® I211AT+I219LM Gigabit LAN)<br>- 1 * 110~240V AC input<br>- 1 * Audio Jack<br>- 1 * Expansion card<br>- 1 * Power button |
| <b>Expansion Interface</b> |                                                                                                                                                                                                                        |
| Expansion                  | - 2 * PCI-E mini card for WIFI or 4G/3G                                                                                                                                                                                |
| <b>Power</b>               |                                                                                                                                                                                                                        |
| Power Input                | - AC version: 100~240V AC                                                                                                                                                                                              |
| <b>Dimensions</b>          |                                                                                                                                                                                                                        |
| Case Dimensions            | - 421*354*91mm                                                                                                                                                                                                         |
| Packing Dimensions         |                                                                                                                                                                                                                        |
| <b>Certifications</b>      |                                                                                                                                                                                                                        |
| Certifications             | - CE, FCC ■ IP65 (Front)                                                                                                                                                                                               |
| <b>Environment</b>         |                                                                                                                                                                                                                        |
| Temperature                | - Operating: -10°C ~ 60°C (with W.T. DRAM/HDD in airflow condition)<br>- Operating: -10°C ~ 60°C (with W.T. DRAM/HDD)<br>- Storage: -20°C ~ 65°C                                                                       |
| Shock                      | - Operating: 15G ■ 11ms duration                                                                                                                                                                                       |
| Vibration                  | - Operating: 5~500Hz/1 Grms                                                                                                                                                                                            |
| <b>Warranty</b>            |                                                                                                                                                                                                                        |
| Warranty                   | - The warranty of 2 years, panel the warranty of 1 year                                                                                                                                                                |