

79.00 EUR

incl. 19% VAT, plus [shipping](#)

- POE !
- Web Interface !
- H.264/H.265 !
- 4 MP !



Support: [Installation](#)

CTFCAM-2 is an IP-camera with manual adjustable zoom (2.8-12mm). The camera is powered via POE-LAN-connector. The camera has a web interface for playback/recording/configuration. She also can be connected to ONVIF compatible video recorders and/or be controlled by ONVIF compatible software.

Specifications :

Image Sensor 4MP: Hi3516D + 1/3" OV4689

Max. Pixels 2592*1520

S/N Ratio >52dB(AGC Off)

LEDs & IR View 5*High Power LED make max 40m IR distance , built in IR-CUT

Lens 4x Optical zoom, (f=2.8-12mm) manual zoom

White Balance ATW / AWB / AWC / MANUAL

Min. Illumination 0.01Lux@F1.2(AGC ON), 0Lux IR on

Day & Night Auto/Color/Black&White/EXT(IR-Cut)

Video Compression H.264+H.265

Bit Rate 0.1Mbps~10Mbps

Electronic Shutter 1/50(1/60)~1/100000 Second

Housing Metal Body+ABS IP66 Weatherproof, Color: White

Network Functions IPv4/RTSP/RTP/RTCP/HTTP/HTTPS/FTP/DHCP/MUDP/SMTP/CIFS/UPNP/PPPOE/NTP/DDNS

Intelligent Alarm Motion Detect/Video Loss/cable offline/ IP address conflict

WDR DWDR, Auto BLC, Auto AGC

Compatibility ONVIF, HIK, DH, XM, etc.

Motion Detection Sensitivity 1~100 adjustable

Max Remote Users 128

Operating System Embedded Linux

Working Humidity 10~90%

Working Temperature Outdoor: -35°C~+60°C

Power Supply : POE (or sepearate DC12V input)

Resource Simultaneous remote monitoring, remote operation & local recording