



69.95 EUR
incl. 19% VAT, plus [shipping](#)

- M.2 NGFF !
- UMTS / 3G !
- LTE (EUROPE) !

Support: [Driver \(Windows\)](#) | [Firmware \(V14\)](#)

The ME906s-158 is a LTE module with NGFF interface , supporting LTE (FDD) B1/B2/B3/B5/B7/B8/B20/B28 ,Penta-band DC-HSPA+/HSPA+/HSPA/WCDMA for Europe network coverage, low power consumption, Global Navigation Satellite System(GNSS), and European carrier certifications, enabling easier and more flexible design and integration into end devices. In addition, the ME906s-158 supports NGFF features to optimize performance, power consumption, and usability.

ME906s-158 is the ideal choice for Ultrabook, notebook, tablet etc.

Manufacturer	Huawei
Model	ME906s-158
Unlocked	Ready for use with global services. No contract required.
Network Bands	<ul style="list-style-type: none"> • LTE (FDD) B1/B2/B3/B5/B7/B8/B20/B28 Quad-band DC-HSPA+/HSPA+/HSPA/UMTS B1/B2/B5/B8 Quad-band EDGE/GPRS/GSM 1900/1800/900/850 MHz GPRS/EDGE: Multi-slot Class 12
Data Speed	WCDMA PS: UL (384 kbps)/ DL (384 kbps) DC-HSPA+ :UL (5.76 Mbps)/ DL (42 Mbps) LTE FDD: UL (50 Mbps)/ DL (150 Mbps) @Bandwidth 20M (CAT4)

Interface	Antenna interfaces x 2 M.2 Socket 2 USB 2.0 interface high speed Power supply UICC interface
Power Supply	Supply voltage range:3.135V~4.4V (3.3 V recommended) Normal operation: -10°C to +55°C
Temp Range	Extended operation: -20°C to +70°C Storage: -40°C to +85°C
GPS	GNSS: GPS Standalone, A-GPS, GPS XTRA, Glonass
Dimensions	<ul style="list-style-type: none">• 42x30x2.3 mm
Supported Systems	Windows 7/Windows 8/Android 4.0 or above SIM Hotswap IPV6 BodySAR
Special Features	Ultrabook feature support(ACT, WiFi Offload , DPTF) Tunable Antenna Supporting MO and MT Supporting formats of PDU Point-to-point and cell broadcast
Package Contents	Huawei ME906s-158 NGFF Embedded Module.