



1189.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Ultra 5 125U !
- TPM2.0 !
- 2 x 2.5GbE !
- Fanless !



- Powered with with Intel® Core™ Ultra 5 125U
- High-Speed Networking: 2 x 2.5GbE for fast and reliable connectivity
- 4K Display: Supports HDMI® 2.0b (4096 x 2160@60Hz) for high-resolution output
- Flexible Storage: 1 x SATA III, 1 x M.2 E-Key, 1 x B+M Key paired with 1 x Nano SIM Slot
- Comprehensive I/O: 4 x RS485/422/232, 3 x USB 3.2 Gen 2, 4 x USB 2.0, 2 x RJ45
- Versatile Mounting: Supports desktop, wall mount, and DIN rail installation

**SYSTEM**

**MB FORM FACTOR**

**CPU**

**CHIPSET**

**MEMORY**

**BIOS**

**WAKE ON LAN**

**WATCHDOG TIMER**

**SECURITY**

**RTC BATTERY**

**OS SUPPORT**

**POWER**

**POWER REQUIREMENT**

**POWER ON MODE**

**DISPLAY**

**Performance**

Onboard Intel® Core™ Ultra 5 Processor 125U (Formerly Meteor Lake, TDP 15W)

Intel® SoC

2 x DDR5 5600MT/s, Dual Channel SO-DIMM, up to 96GB

UEFI

Yes

255 Levels

TPM2.0

Lithium Battery

Windows® 11 (64bit)

Windows® 10 (64bit)

Linux

DC-in 12~36V

90W Adapter: AC90~240V, DC19V/4.7A

AT / ATX (Default) Mode

---

GPU	Intel® Graphics
Type C DP	1 x Type C DP1.4 (Max Resolution: 4096 x 2160@60Hz)
DP	2 x DP1.4 (Max Resolution: 4096 x 2160@60Hz)
HDMI	2 x HDMI 2.0b (Max Resolution: 4096 x 2160@60Hz)
MULTIPLE DISPLAY	Support 3 Displays
AUDIO	
CODEC	Realtek Audio Codec
AMPLIFIER	3W
LAN	
ETHERNET	1 x RJ45 for Intel® I226-V 2.5GbE 1 x RJ45 for Intel® I226-LM 2.5GbE
SYSTEM I/O	
	4 x Antenna Holes 1 x DC-in 1 x HDMI® 2.0b 1 x DP 3 x USB 3.2 Gen 2 1 x USB 3.2 Gen 1 Type-C 2 x RJ45 1 x GND Hold 1 x Power Button 1 x Reset Button 1 x Power LED
REAR PANEL I/O	1 x HDD LED 4 x USB 2.0 4 x RS-232/422/485 2 x Antenna Holes
FRONT PANEL I/O	
EXPANSION	
M.2	1 x E-Key 2230 (USB 2.0/PCIe 3.0 x1) Support CNVi 1 x B-Key 3042/3052 (USB 3.2/PCIe 3.0 x2) 1 x M-Key 2242/2280 (PCIe 4.0 x4 / SATA III) Support NVMe 1 x Nano SIM Card Slot
SIM	
MECHANICAL	
MOUNTING	Desktop, Wallmount, Din Rail
DIMENSIONS (W x D x H)	185.0 (W) x 142.0 (D) x 61.0 (H) mm (7.28" x 5.6" x 2.4")
NET WEIGHT	3.5 kg
ENVIRONMENT & CERTIFICATION	
OPERATING TEMPERATURE	-20°C ~ 60°C (-4°F ~ 140°F)
STORAGE TEMPERATURE	-40°C ~ 85°C (-40°F ~ 185°F)
OPERATING HUMIDITY	10 ~ 90% Relative Humidity, Non-condensing
CERTIFICATION	CE/FCC Class A LVD